

TANGO

As with all quality carpets, slight variation in colour may vary from dye lot to dye lot. It is recommended that this carpet be laid in accordance with AS2455. Seam Sealer must be used on all seams. For conventional installation heavy duty underlay is recommended. Alternatively, a dual bond or direct stick installation can be used. Protective chair pads are recommended under office chairs with roller casters to preserve the appearance and avoid premature wear. Professional cleaning is recommended. Construction of this carpet may involve the occurrence of shading / permanent pile reversal. Certain light sources shining across the surface may emphasise the effect of shading / permanent pile reversal. This occurrence cannot be predicted or prevented – it is not a manufacturing defect and will not detract from the carpet performance. Since carpet is a textile material, a perfect pattern match on the linear pattern cannot be guaranteed.

George Low reserves the right to modify specifications subject to manufacturing variances. Manufacturing processes may necessitate specification changes without prior notice and without prejudice.

Made in Australia

Pile Fibre	100% Solution Dyed Nylon
Yarn Structure	Cut Pile
Colouration	Solution Dyed
Machine Gauge	1/8
Pile Height	9 mm (+/- 5%)
Width	3.66 m
Tufted Pile Weight	30 oz/yd ² . 1017 g/m ² (+/- 5%)
Primary Backing	Woven Synthetic
Secondary Backing	Easybac
Insect Resistance	To Australian Standard
Average Tuft Bind	Exceeds C.I.A. requirements AS2111.15
Backing Bond Strength	Exceeds C.I.A. requirements AS2111.16
Fire Rating	ASISO 9239.1-2003
CHF Value	3.1 kW/m ²
Smoke Value	93 % min
Pattern Repeat	None
Rating	Residential Heavy Duty

Warranties/Features

- **5 Year Limited Wear**
- **Warm Neutral Colours**
- **Cut Pile**

George Low of Melbourne Pty Ltd

Telephone: (03) 9587 4222 Facsimile: (03) 9587 4525 www.georgelow.com.au sales@georgelow.com.au