

Seal & Bond

Special Primer



**FAST, MULTIFUNCTIONAL
ADHESIVE PRIMER
FOR MATERIALS THAT ARE
DIFFICULT TO GLUE**



- Ideal for Polypropylene (PP), Polyethylene (PE), Acrylonitrile butadiene styrene (ABS), powder coatings, teflon and other painted surfaces
- Can be used for glue, tapes and coatings
- Transparent
- Does not leave traces or stains
- Fast and easy to apply
- Dries fast
- Economic in use

SOLE AGENTS IN AUSTRALIA & NEW ZEALAND

Olmurtech
Adhesives • Sealants • Cleaners



PROPERTIES

- Seal & Bond Special Primer guarantees a better bonding on synthetic materials, powder coating and painted surfaces
- Seal & Bond Special Primer combines a high elasticity with a fast drying time, After +/- 10 minutes gluing is possible
- Seal & Bond Special Primer is to be applied directly on the surface that needs to be glued. Because of the application of the primer the surface is ideal for bonding MS Polymers, silicones, tapes and paints

TECHNICAL INFORMATION

Before using Seal & Bond Special Primer, perform a bonding test on the substrates

Colour: Transparent

Base: Polyolefin

Storage conditions: temperature range 10° up to 25° and a max. humidity degree of 60%

Consumption: +/- 2-3 m² per 400ml, +/- 1-1/2 m² per 150ml

Drying time: +/- 10 min

VOC value: 276,4g/l

Surfaces: Polypropylene (PP), Polyethylene (PE) / Ethylene Propylene Diene Monomer (EPDM rubber), Acrylonitrile Butadiene Styrene (ABS), Styrene Acrylonitrile (SAN-PC), Polyamides (PA), Polyurethane and Reaction Injection Moulding (PUR-RIM), R-TRU, polyphenylene Oxide (PPO), Polybutylene Terephthalate (PBT), PUR flexible foam, UP-GF Plastics

Powder Coatings, Painted Surfaces

Safety Measurements: Please consult the safety data sheet

Shelf life: 36 months from date of manufacture

Seal & Bond Special Primer is 100% free of heavy metals. The aerosols are made of recycled materials and only contain a CFC-free propellant

USE

Application Uses:

Improves bonding of difficult materials to glue such as: synthetic materials, powder coating, teflon coated and other painted surfaces, aluminium and many more

Application Instructions:

- Clean surface first with Multiclean
- Ensure surface is dry
- Shake before use approx 2-3 min (make sure you hear the mixing ball)
- Spray in one thin layer
- Let dry for 10 min. at a temperature of 20°c
- Glue, tape, paint can be applied after +/- 10 min