

SAFETY DATA SHEET

Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) No 2015/830

SEAL & BOND SPECIAL PRIMER

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : SEAL & BOND SPECIAL PRIMER
Registration number REACH : Not applicable (mixture)
Product type REACH : Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant identified uses

Primer

1.2.2 Uses advised against

No uses advised against known

1.3. Details of the supplier of the safety data sheet

Supplier of the safety data sheet

Novatio*
Industrielaan 5B
B-2250 Olen
☎ +32 14 25 76 40
☎ +32 14 22 02 66
info@novatio.be
*Novatio is a registered trademark of Novatech International
Industrielaan 5B

Manufacturer of the product

Novatech International N.V.
Industrielaan 5B
B-2250 Olen
☎ +32 14 85 97 37
☎ +32 14 85 97 38
info@tec7.be

Distributor of the product

Olmurtech
P.O. Box 5939
Brendale DC, QLD. 4500
Australia
☎ +61 0 426 177 310
www.olmurtech.com.au

1.4. Emergency telephone number

New Zealand National Poisons Centre
24 hour contact within NZ ☎ 0800 764 766 (0800POISON)
24 hour contact from outside NZ ☎ +64 3 479 7248

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

Class	Category	Hazard statements
Aerosol	category 1	H222: Extremely flammable aerosol.
Aerosol	category 1	H229: Pressurised container: May burst if heated.
Skin Irrit.	category 2	H315: Causes skin irritation.
STOT SE	category 3	H336: May cause drowsiness or dizziness.
Aquatic Chronic	category 2	H411: Toxic to aquatic life with long lasting effects.

2.2. Label elements

SEAL & BOND SPECIAL PRIMER



Contains: naphtha (petroleum), hydrotreated light.

Signal word Danger

H-statements

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

P-statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P280 Wear protective gloves, protective clothing and eye protection/face protection.
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122°F.

2.3. Other hazards

No other hazards known

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name REACH Registration No	CAS No EC No	Conc. (C)	Classification according to CLP	Note	Remark
naphtha (petroleum), hydrotreated light 01-2119475133-43	64742-49-0 265-151-9	50%<C<75%	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Chronic 2; H411	(1)(2)(10)	Constituent
dimethyl ether 01-2119472128-37	115-10-6 204-065-8	25%<C<50%	Flam. Gas 1; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)	Propellant
xylene 01-2119488216-32	1330-20-7 215-535-7	5%<C<10%	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315	(1)(2)(10)	Constituent

(1) For H-statements in full: see heading 16

(2) Substance with a Community workplace exposure limit

(10) Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

SECTION 4: First aid measures

4.1. Description of first aid measures

General:

If you feel unwell, seek medical advice.

After inhalation:

Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.

After skin contact:

Wash immediately with lots of water. Soap may be used. Take victim to a doctor if irritation persists.

After eye contact:

Rinse with water. Do not apply neutralizing agents. Take victim to an ophthalmologist if irritation persists.

After ingestion:

Rinse mouth with water. Consult a doctor/medical service if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

4.2.1 Acute symptoms

Reason for revision: CLP-ATP4-II

Publication date: 2010-12-08

Date of revision: 2015-05-13

Revision number: 0200

Product number: 50486

2 / 16

SEAL & BOND SPECIAL PRIMER

After inhalation:

EXPOSURE TO HIGH CONCENTRATIONS: Irritation of the nasal mucous membranes. Central nervous system depression. Headache. Dizziness. Narcosis.

After skin contact:

Tingling/irritation of the skin.

After eye contact:

No effects known.

After ingestion:

No effects known.

4.2.2 Delayed symptoms

No effects known.

4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

SECTION 5: Firefighting measures

5.1. Extinguishing media

5.1.1 Suitable extinguishing media:

Water spray. Alcohol-resistant foam. BC powder. Carbon dioxide.

5.1.2 Unsuitable extinguishing media:

Solid water jet ineffective as extinguishing medium.

5.2. Special hazards arising from the substance or mixture

Upon combustion: CO and CO₂ are formed.

5.3. Advice for firefighters

5.3.1 Instructions:

If exposed to fire cool the closed containers by spraying with water. Physical explosion risk: extinguish/cool from behind cover. Do not move the load if exposed to heat. After cooling: persistent risk of physical explosion. Take account of environmentally hazardous firefighting water. Use water moderately and if possible collect or contain it.

5.3.2 Special protective equipment for fire-fighters:

Gloves. Protective goggles. Head/neck protection. Protective clothing. Heat/fire exposure: compressed air/oxygen apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment.

6.1.1 Protective equipment for non-emergency personnel

See heading 8.2

6.1.2 Protective equipment for emergency responders

Gloves. Protective goggles. Head/neck protection. Protective clothing.

Suitable protective clothing

See heading 8.2

6.2. Environmental precautions

Dam up the liquid spill.

6.3. Methods and material for containment and cleaning up

Take up liquid spill into absorbent material. Scoop absorbed substance into closing containers. Carefully collect the spill/leftovers. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

6.4. Reference to other sections

See heading 13.

SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

7.1. Precautions for safe handling

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Observe normal hygiene standards. Remove contaminated clothing immediately.

7.2. Conditions for safe storage, including any incompatibilities

7.2.1 Safe storage requirements:

Storage temperature: < 50 °C. Ventilation at floor level. Fireproof storeroom. Keep out of direct sunlight. Meet the legal requirements.

7.2.2 Keep away from:

SEAL & BOND SPECIAL PRIMER

Heat sources, ignition sources.

7.2.3 Suitable packaging material:

Aerosol.

7.2.4 Non suitable packaging material:

No data available

7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 Occupational exposure

a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

EU

Dimethylether	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	1000 ppm
	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	1920 mg/m ³
Xylene, mixed isomers, pure	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	50 ppm
	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	221 mg/m ³
	Short time value (Indicative occupational exposure limit value)	100 ppm
	Short time value (Indicative occupational exposure limit value)	442 mg/m ³

Belgium

Huiles minérales (brouillards)	Time-weighted average exposure limit 8 h	5 mg/m ³
	Short time value	10 mg/m ³
Oxyde de diméthyle	Time-weighted average exposure limit 8 h	1000 ppm
	Time-weighted average exposure limit 8 h	1920 mg/m ³
Xylène, isomères mixtes, purs	Time-weighted average exposure limit 8 h	50 ppm
	Time-weighted average exposure limit 8 h	221 mg/m ³
	Short time value	100 ppm
	Short time value	442 mg/m ³

The Netherlands

Dimethylether	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	496 ppm
	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	950 mg/m ³
	Short time value (Public occupational exposure limit value)	783 ppm
	Short time value (Public occupational exposure limit value)	1500 mg/m ³
Olienevel (minerale olie)	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	5 mg/m ³
Xyleen (o-,m- en p-isomeren)	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	48 ppm
	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	210 mg/m ³
	Short time value (Public occupational exposure limit value)	100 ppm
	Short time value (Public occupational exposure limit value)	442 mg/m ³

France

Oxyde de diméthyle	Time-weighted average exposure limit 8 h (VRI: Valeur réglementaire indicative)	1000 ppm
	Time-weighted average exposure limit 8 h (VRI: Valeur réglementaire indicative)	1920 mg/m ³
Xylènes, isomères mixtes, purs	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	50 ppm
	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	221 mg/m ³
	Short time value (VRC: Valeur réglementaire contraignante)	100 ppm
	Short time value (VRC: Valeur réglementaire contraignante)	442 mg/m ³

Germany

Reason for revision: CLP-ATP4-II

Publication date: 2010-12-08

Date of revision: 2015-05-13

Revision number: 0200

Product number: 50486

4 / 16

SEAL & BOND SPECIAL PRIMER

Dimethylether	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	1900 mg/m ³

UK

Dimethyl ether	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	400 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	766 mg/m ³
	Short time value (Workplace exposure limit (EH40/2005))	500 ppm
	Short time value (Workplace exposure limit (EH40/2005))	958 mg/m ³
Xylene, o-,m-,p- or mixed isomers	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	50 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	220 mg/m ³
	Short time value (Workplace exposure limit (EH40/2005))	100 ppm
	Short time value (Workplace exposure limit (EH40/2005))	441 mg/m ³

USA (TLV-ACGIH)

Mineral oil, pure, highly and severely refined	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	5 mg/m ³ (l)
Xylene (all isomers)	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	100 ppm
	Short time value (TLV - Adopted Value)	150 ppm

(l): Inhalable fraction

b) National biological limit values

If limit values are applicable and available these will be listed below.

8.1.2 Sampling methods

If applicable and available it will be listed below.

Oil Mist (Mineral)	NIOSH	5026
Xylene (Volatile Organic compounds)	NIOSH	2549

8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

8.1.4 DNEL/PNEC values

DNEL/DMEL - Workers

xylene

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	77 mg/m ³	
	Acute systemic effects inhalation	289 mg/m ³	
	Acute local effects inhalation	289 mg/m ³	
	Long-term systemic effects dermal	180 mg/kg bw/day	

DNEL/DMEL - General population

xylene

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	14.8 mg/m ³	
	Acute systemic effects inhalation	174 mg/m ³	
	Acute local effects inhalation	174 mg/m ³	
	Long-term systemic effects dermal	108 mg/kg bw/day	
	Long-term systemic effects oral	1.6 mg/kg bw/day	

PNEC

xylene

Compartments	Value	Remark
Fresh water	0.327 mg/l	
Marine water	0.327 mg/l	
STP	6.58 mg/l	
Fresh water sediment	12.46 mg/kg sediment dw	
Marine water sediment	12.46 mg/kg sediment dw	
Soil	2.31 mg/kg soil dw	

8.1.5 Control banding

If applicable and available it will be listed below.

8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

8.2.1 Appropriate engineering controls

Reason for revision: CLP-ATP4-II

Publication date: 2010-12-08

Date of revision: 2015-05-13

Revision number: 0200

Product number: 50486

5 / 16

SEAL & BOND SPECIAL PRIMER

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Measure the concentration in the air regularly.

8.2.2 Individual protection measures, such as personal protective equipment

Observe normal hygiene standards. Do not eat, drink or smoke during work.

a) Respiratory protection:

Wear gas mask with filter type A if conc. in air > exposure limit.

b) Hand protection:

Gloves.

c) Eye protection:

Protective goggles.

d) Skin protection:

Head/neck protection. Protective clothing.

8.2.3 Environmental exposure controls:

See headings 6.2, 6.3 and 13

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical form	Aerosol
Odour	Characteristic odour
Odour threshold	No data available
Colour	Variable in colour, depending on the composition
Particle size	No data available
Explosion limits	0.6 - 26.2 vol %
Flammability	Extremely flammable aerosol.
Log Kow	Not applicable (mixture)
Dynamic viscosity	No data available
Kinematic viscosity	No data available
Melting point	No data available
Boiling point	No data available
Flash point	No data available
Evaporation rate	No data available
Relative vapour density	> 1
Vapour pressure	4000 hPa
Solubility	insoluble
Relative density	0.70 ; 20 °C
Decomposition temperature	No data available
Auto-ignition temperature	No data available
Explosive properties	No chemical group associated with explosive properties
Oxidising properties	No chemical group associated with oxidising properties
pH	No data available

9.2. Other information

Absolute density	707 kg/m ³ ; 20 °C
------------------	-------------------------------

SECTION 10: Stability and reactivity

10.1. Reactivity

May be ignited by sparks.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks.

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

Upon combustion: CO and CO₂ are formed.

SEAL & BOND SPECIAL PRIMER

SECTION 11: Toxicological information

11.1. Information on toxicological effects

11.1.1 Test results

Acute toxicity

SEAL & BOND SPECIAL PRIMER

No (test)data on the mixture available

naphtha (petroleum), hydrotreated light

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	> 5000 mg/kg bw		Rat (male/female)	Experimental value	
Dermal	LD50	Equivalent to OECD 402	> 2000 mg/kg bw	24 h	Rabbit (male/female)	Experimental value	
Inhalation (vapours)	LC50	Equivalent to OECD 403	> 5610 mg/m ³ air	4 h	Rat (male/female)	Calculated value	

xylene

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to EU Method B.1	3523 mg/kg bw		Rat (male)	Experimental value	
Dermal			category 4			Annex VI	
Inhalation (vapours)			category 4			Annex VI	

Judgement is based on the relevant ingredients

Conclusion

Not classified for acute toxicity

Corrosion/irritation

SEAL & BOND SPECIAL PRIMER

No (test)data on the mixture available

naphtha (petroleum), hydrotreated light

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	Equivalent to OECD 405		24; 48; 72 hours	Rabbit	Experimental value	Single treatment
Skin	Irritating	OECD 404	4 h	1; 24; 48; 72; 168 hours	Rabbit	Experimental value	
Inhalation (vapours)	Not irritating		1 h		Human	Experimental value	

xylene

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Moderately irritating	Draize Test		24; 48; 72 hours	Rabbit	Experimental value	
Skin	Moderately irritating	Draize Skin Test	24 h - 72 h	24; 72 hours	Rabbit	Experimental value	
Inhalation (vapours)	Irritating		4 h		Human		

Classification is based on the relevant ingredients

Conclusion

Causes skin irritation.

Not classified as irritating to the eyes

Respiratory or skin sensitisation

SEAL & BOND SPECIAL PRIMER

No (test)data on the mixture available

naphtha (petroleum), hydrotreated light

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Equivalent to OECD 406	6 h	24; 48 hours	Guinea pig (male)	Experimental value	

Reason for revision: CLP-ATP4-II

Publication date: 2010-12-08

Date of revision: 2015-05-13

Revision number: 0200

Product number: 50486

7 / 16

SEAL & BOND SPECIAL PRIMER

xylene

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	OECD 429			Mouse	Experimental value	

Judgement is based on the relevant ingredients

Conclusion

Not classified as sensitizing for skin

Specific target organ toxicity

SEAL & BOND SPECIAL PRIMER

No (test)data on the mixture available

naphtha (petroleum), hydrotreated light

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral	NOEL	Subacute toxicity test	< 500 mg/kg bw/day	Kidney	No effect	4 weeks (5 days/week)	Rat (male)	Experimental value
Dermal	NOAEL local effects	Equivalent to OECD 410	< 200 mg/kg bw/day	Skin	No effect	4 weeks (6h/day, 3 days/week)	Rabbit (male/female)	Experimental value
Inhalation (vapours)	NOAEC	Equivalent to OECD 453	1402 mg/m ³ air	General	No effect	107 weeks (6h/day, 5 days/week) - 109 weeks (6h/day, 5 days/week)	Rat (male/female)	Experimental value
Inhalation (vapours)	LOAEL		4320 mg/m ³ air	Central nervous system	neurotoxic effects	1 h	Human (male/female)	Experimental value

xylene

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (stomach tube)	LOAEL	Equivalent to OECD 408	150 mg/kg bw/day	Liver	Weight gain	90 days (1x/day)	Rat (male)	Experimental value
Oral (stomach tube)	NOAEL	Equivalent to OECD 408	150 mg/kg bw/day	Liver	No effect	90 days (1x/day)	Rat (female)	Experimental value
Inhalation (vapours)	NOAEC	Subchronic toxicity test	≥ 3515 mg/m ³		No effect	13 weeks (6h/day, 5 days/week)	Rat (male)	Experimental value

Classification is based on the relevant ingredients

Conclusion

May cause drowsiness or dizziness.

Not classified for subchronic toxicity

Mutagenicity (in vitro)

SEAL & BOND SPECIAL PRIMER

No (test)data on the mixture available

naphtha (petroleum), hydrotreated light

Result	Method	Test substrate	Effect	Value determination
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 476	Mouse (lymphoma L5178Y cells)	No effect	Experimental value
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value

xylene

Result	Method	Test substrate	Effect	Value determination
Negative with metabolic activation, negative without metabolic activation	Equivalent or similar to EU Method B.10	Chinese hamster ovary (CHO)		Experimental value
Negative with metabolic activation, negative without metabolic activation	Equivalent to EU Method B.19	Chinese hamster ovary (CHO)		Experimental value

Mutagenicity (in vivo)

SEAL & BOND SPECIAL PRIMER

No (test)data on the mixture available

naphtha (petroleum), hydrotreated light

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative	Equivalent to OECD 475	5 day(s)	Rat (male)		Experimental value

Reason for revision: CLP-ATP4-II

Publication date: 2010-12-08

Date of revision: 2015-05-13

Revision number: 0200

Product number: 50486

8 / 16

SEAL & BOND SPECIAL PRIMER

xylene

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative	Equivalent to OECD 478		Mouse (male/female)		Experimental value

Judgement is based on the relevant ingredients

Conclusion

Not classified for mutagenic or genotoxic toxicity

Carcinogenicity

SEAL & BOND SPECIAL PRIMER

No (test) data on the mixture available

naphtha (petroleum), hydrotreated light

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Dermal	NOAEL	Equivalent to OECD 451	0.05 ml	102 weeks (3 times/week)	Mouse (male)	No carcinogenic effect		Experimental value

xylene

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Oral	Dose level	Equivalent to EU Method B.32	≥ 500 mg/kg bw/day	103 weeks (5 days/week)	Rat (male/female)	No carcinogenic effect		Experimental value

Judgement is based on the relevant ingredients

Conclusion

Not classified for carcinogenicity

Reproductive toxicity

SEAL & BOND SPECIAL PRIMER

No (test) data on the mixture available

naphtha (petroleum), hydrotreated light

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity	NOAEL	Equivalent to OECD 414	23900 mg/m ³ air	14 days (6h/day)	Rat	No effect	Foetus	Experimental value
Maternal toxicity	NOAEL	Equivalent to OECD 414	23900 mg/m ³ air	14 day(s)	Rat	No effect		Experimental value
Effects on fertility	NOAEC (P/F1)	Equivalent to OECD 416	≥ 20000 mg/m ³ air	10 weeks (6h/day, 7 days/week)	Rat (male/female)	No effect		Experimental value

xylene

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity	NOAEC	Equivalent to OECD 414	100 ppm	15 days (6h/day)	Rat (male/female)	No effect		Experimental value
Maternal toxicity	NOAEC	OECD 414	500 ppm	15 days (6h/day)	Rat	No effect		Experimental value
Effects on fertility	NOAEC (P)	EPA OPPTS 870.3800	≥ 500 ppm	70 days (6h/day)	Rat (male/female)	No effect		Experimental value
	NOAEC (F1)	EPA OPPTS 870.3800	≥ 500 ppm	70 days (6h/day)	Rat (male/female)	No effect		Experimental value

Judgement is based on the relevant ingredients

Conclusion

Not classified for reprotoxic or developmental toxicity

Toxicity other effects

SEAL & BOND SPECIAL PRIMER

No (test) data on the mixture available

Chronic effects from short and long-term exposure

SEAL & BOND SPECIAL PRIMER

No effects known.

Reason for revision: CLP-ATP4-II

Publication date: 2010-12-08

Date of revision: 2015-05-13

Revision number: 0200

Product number: 50486

9 / 16

SEAL & BOND SPECIAL PRIMER

SECTION 12: Ecological information

12.1. Toxicity

SEAL & BOND SPECIAL PRIMER

No (test)data on the mixture available

naphtha (petroleum), hydrotreated light

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LL50	OECD 203	10 mg/l	96 h	Oncorhynchus mykiss	Semi-static system	Fresh water	Experimental value; GLP
Acute toxicity crustacea	EL50	OECD 202	4.5 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; GLP
Toxicity algae and other aquatic plants	EL50	OECD 201	3.1 mg/l	72 h	Pseudokirchneria lla subcapitata	Static system	Fresh water	Experimental value; GLP
Long-term toxicity fish	NOELR	OECD 204	2.6 mg/l	14 day(s)	Pimephales promelas	Semi-static system	Fresh water	Experimental value; GLP
Long-term toxicity aquatic crustacea	NOELR	OECD 211	2.6 mg/l	21 day(s)	Daphnia magna	Semi-static system	Fresh water	Experimental value; GLP
Toxicity aquatic micro-organisms	EC50		15.41 mg/l	40 h	Tetrahymena pyriformis		Fresh water	QSAR; Growth inhibition

xylene

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	OECD 203	2.6 mg/l	96 h	Oncorhynchus mykiss	Static system	Fresh water	Read-across; Lethal
Acute toxicity crustacea	EC50		3.82 mg/l	48 h	Daphnia magna	Flow-through system	Fresh water	Read-across
Toxicity algae and other aquatic plants	EC50	OECD 201	4.36 mg/l	73 h	Pseudokirchneria lla subcapitata	Static system	Fresh water	Experimental value; Growth rate
Long-term toxicity fish	NOEC		> 1.3 mg/l	56 day(s)	Oncorhynchus mykiss	Flow-through system	Fresh water	Experimental value; Lethal
Long-term toxicity aquatic crustacea	NOEC	US EPA	1.17 mg/l	7 day(s)	Ceriodaphnia dubia		Fresh water	Read-across; Reproduction

Classification is based on the relevant ingredients

Conclusion

Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

naphtha (petroleum), hydrotreated light

Biodegradation water

Method	Value	Duration	Value determination
OECD 301D: Closed Bottle Test	9 %; GLP	28 day(s)	Experimental value

xylene

Biodegradation water

Method	Value	Duration	Value determination
OECD 301: Ready Biodegradability	100 %	12 day(s)	Experimental value
OECD 301F: Manometric Respirometry Test	87.8 %; GLP	28 day(s)	Read-across

Conclusion

Contains non readily biodegradable component(s)

12.3. Bioaccumulative potential

SEAL & BOND SPECIAL PRIMER

Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

SEAL & BOND SPECIAL PRIMER

naphtha (petroleum), hydrotreated light

BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF		12.6 - 223.87; Calculated value		Pimephales promelas	Read-across

Log Kow

Method	Remark	Value	Temperature	Value determination
OECD 117		2.4 - 5.7	23 °C	Experimental value

xylene

BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF		7 - 26	8 week(s)	Oncorhynchus mykiss	Experimental value

Log Kow

Method	Remark	Value	Temperature	Value determination
		3.2	20 °C	Conclusion by analogy

Conclusion

Does not contain bioaccumulative component(s)

12.4. Mobility in soil

naphtha (petroleum), hydrotreated light

(log) Koc

Parameter	Method	Value	Value determination
log Koc	SRC PCKOCWIN v1.66	1.783 - 2.36	Calculated value

Percent distribution

Method	Fraction air	Fraction biota	Fraction sediment	Fraction soil	Fraction water	Value determination
Mackay level III	93.02 %		0.81 %	0.34 %	5.83 %	Calculated value

Conclusion

Contains component(s) with potential for mobility in the soil

12.5. Results of PBT and vPvB assessment

Does not contain component(s) that meet(s) the criteria of PBT and/or vPvB as listed in Annex XIII of Regulation (EC) No 1907/2006.

12.6. Other adverse effects

SEAL & BOND SPECIAL PRIMER

Fluorinated greenhouse gases (Regulation (EU) No 517/2014)

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

naphtha (petroleum), hydrotreated light

Ground water

Ground water pollutant

xylene

Ground water

Ground water pollutant

SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

13.1. Waste treatment methods

13.1.1 Provisions relating to waste

European Union

Hazardous waste according to Directive 2008/98/EC.

Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

08 01 11* (wastes from MFSU and removal of paint and varnish: waste paint and varnish containing organic solvents or other hazardous substances).

Depending on branch of industry and production process, also other waste codes may be applicable.

13.1.2 Disposal methods

Recycle/reuse. Specific treatment. Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Do not discharge into drains or the environment.

Reason for revision: CLP-ATP4-II

Publication date: 2010-12-08

Date of revision: 2015-05-13

Revision number: 0200

Product number: 50486

11 / 16

SEAL & BOND SPECIAL PRIMER

13.1.3 Packaging/Container

European Union

Waste material code packaging (Directive 2008/98/EC).

15 01 10* (packaging containing residues of or contaminated by dangerous substances).

SECTION 14: Transport information

Road (ADR)

14.1. UN number

UN number	1950
-----------	------

14.2. UN proper shipping name

Proper shipping name	Aerosols
----------------------	----------

14.3. Transport hazard class(es)

Hazard identification number	
Class	2
Classification code	5F

14.4. Packing group

Packing group	
Labels	2.1

14.5. Environmental hazards

Environmentally hazardous substance mark	yes
--	-----

14.6. Special precautions for user

Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

Rail (RID)

14.1. UN number

UN number	1950
-----------	------

14.2. UN proper shipping name

Proper shipping name	Aerosols
----------------------	----------

14.3. Transport hazard class(es)

Hazard identification number	23
Class	2
Classification code	5F

14.4. Packing group

Packing group	
Labels	2.1

14.5. Environmental hazards

Environmentally hazardous substance mark	yes
--	-----

14.6. Special precautions for user

Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

Inland waterways (ADN)

14.1. UN number

UN number	1950
-----------	------

14.2. UN proper shipping name

Proper shipping name	Aerosols
----------------------	----------

14.3. Transport hazard class(es)

Class	2
Classification code	5F

14.4. Packing group

Packing group	
Labels	2.1

14.5. Environmental hazards

Reason for revision: CLP-ATP4-II

Publication date: 2010-12-08

Date of revision: 2015-05-13

Revision number: 0200

Product number: 50486

12 / 16

SEAL & BOND SPECIAL PRIMER

Environmentally hazardous substance mark	yes
14.6. Special precautions for user	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

Sea (IMDG/IMSBC)

14.1. UN number	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	Aerosols
14.3. Transport hazard class(es)	
Class	2.1
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Marine pollutant	P
Environmentally hazardous substance mark	yes
14.6. Special precautions for user	
Special provisions	63
Special provisions	190
Special provisions	277
Special provisions	327
Special provisions	344
Special provisions	959
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)
14.7. Transport in bulk according to Annex II of Marpol and the IBC Code	
Annex II of MARPOL 73/78	Not applicable

Air (ICAO-TI/IATA-DGR)

14.1. UN number	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	Aerosols, flammable
14.3. Transport hazard class(es)	
Class	2.1
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Environmentally hazardous substance mark	yes
14.6. Special precautions for user	
Special provisions	A145
Special provisions	A167
Special provisions	A802
limited quantities: maximum net quantity per packaging	30 kg G

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European legislation:

VOC content Directive 2010/75/EU

VOC content	Remark
99.07 %	
700.4 g/l	

Indicative occupational exposure limit values (Directive 98/24/EC, 2000/39/EC and 2009/161/EU)

Product name	Skin resorption

Reason for revision: CLP-ATP4-II

Publication date: 2010-12-08

Date of revision: 2015-05-13

Revision number: 0200

Product number: 50486

13 / 16

SEAL & BOND SPECIAL PRIMER

Xylene, mixed isomers, pure

Skin

REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

	Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
· naphtha (petroleum), hydrotreated light	Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F; (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10; (c) hazard class 4.1; (d) hazard class 5.1.	1. Shall not be used in: — ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, — tricks and jokes, — games for one or more participants, or any article intended to be used as such, even with ornamental aspects.2. Articles not complying with paragraph 1 shall not be placed on the market.3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they: — can be used as fuel in decorative oil lamps for supply to the general public, and, — present an aspiration hazard and are labelled with R65 or H304.4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN).5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met: a) lamp oils, labelled with R65 or H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: “Keep lamps filled with this liquid out of the reach of children”; and, by 1 December 2010, “Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life-threatening lung damage”; b) grill lighter fluids, labelled with R65 or H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: “Just a sip of grill lighter may lead to life threatening lung damage”; c) lamp oils and grill lighters, labelled with R65 or H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.6. No later than 1 June 2014, the Commission shall request the European Chemicals Agency to prepare a dossier, in accordance with Article 69 of the present Regulation with a view to ban, if appropriate, grill lighter fluids and fuel for decorative lamps, labelled R65 or H304, intended for supply to the general public.7. Natural or legal persons placing on the market for the first time lamp oils and grill lighter fluids, labelled with R65 or H304, shall by 1 December 2011, and annually thereafter, provide data on alternatives to lamp oils and grill lighter fluids labelled R65 or H304 to the competent authority in the Member State concerned. Member States shall make those data available to the Commission.’
· naphtha (petroleum), hydrotreated light · xylene	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to that Regulation or not.	1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following: — metallic glitter intended mainly for decoration, — artificial snow and frost, — “whoopee” cushions, — silly string aerosols, — imitation excrement, — horns for parties, — decorative flakes and foams, — artificial cobwebs, — stink bombs.2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with: “For professional users only”.3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/ 324/EEC.4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.

National legislation Belgium

SEAL & BOND SPECIAL PRIMER

No data available

xylene

Résorption peau	Xylène, isomères mixtes, purs; D; La mention “D” signifie que la résorption de l’agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l’exposition totale. Cette résorption peut se faire tant par contact direct que par présence de l’agent dans l’air.
-----------------	--

National legislation The Netherlands

SEAL & BOND SPECIAL PRIMER

Waste identification (the Netherlands)	LWCA (the Netherlands): KGA category 06
--	---

xylene

Huidopname (wettelijk)	Xyleen (o-,m- en p-isomeren); H
SZW - Lijst van voor de voortplanting giftige stoffen (ontwikkeling)	xyleen; 2; Suspected of damaging the unborn child.

National legislation France

Reason for revision: CLP-ATP4-II

Publication date: 2010-12-08

Date of revision: 2015-05-13

Revision number: 0200

Product number: 50486

14 / 16

SEAL & BOND SPECIAL PRIMER

SEAL & BOND SPECIAL PRIMER

No data available

xylene

VME - Risque de pénétration percutanée	Xylènes, isomères mixtes, purs; PP
--	------------------------------------

National legislation Germany

SEAL & BOND SPECIAL PRIMER

WGK	3; Classification water polluting based on the components in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS) of 27 July 2005 (Anhang 4)
-----	---

naphtha (petroleum), hydrotreated light

TA-Luft	5.2.5; I
---------	----------

dimethyl ether

TA-Luft	5.2.5
---------	-------

xylene

TA-Luft	5.2.5; I
---------	----------

National legislation United Kingdom

SEAL & BOND SPECIAL PRIMER

No data available

xylene

Skin absorption	Xylene, o-,m-,p- or mixed isomers; Sk
-----------------	---------------------------------------

Other relevant data

SEAL & BOND SPECIAL PRIMER

No data available

naphtha (petroleum), hydrotreated light

TLV - Carcinogen	Mineral oil, pure, highly and severely refined; A4
------------------	--

xylene

TLV - Carcinogen	Xylene (all isomers); A4
------------------	--------------------------

IARC - classification	3; Xylenes
-----------------------	------------

15.2. Chemical safety assessment

No chemical safety assessment has been conducted for the mixture.

SECTION 16: Other information

Full text of any H-statements referred to under headings 2 and 3:

H220 Extremely flammable gas.
H222 Extremely flammable aerosol.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H229 Pressurised container: May burst if heated.
H280 Contains gas under pressure; may explode if heated.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H332 Harmful if inhaled.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

(*)	INTERNAL CLASSIFICATION BY BIG
CLP (EU-GHS)	Classification, labelling and packaging (Globally Harmonised System in Europe)
DMEL	Derived Minimal Effect Level
DNEL	Derived No Effect Level
EC50	Effect Concentration 50 %
ERC50	EC50 in terms of reduction of growth rate
LC50	Lethal Concentration 50 %
LD50	Lethal Dose 50 %
NOAEL	No Observed Adverse Effect Level
NOEC	No Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent, Bioaccumulative & Toxic
PNEC	Predicted No Effect Concentration
STP	Sludge Treatment Process
vPvB	very Persistent & very Bioaccumulative

Reason for revision: CLP-ATP4-II

Publication date: 2010-12-08

Date of revision: 2015-05-13

Revision number: 0200

Product number: 50486

15 / 16

SEAL & BOND SPECIAL PRIMER

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Old versions must be destroyed. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.